

DATA SHEET

VOCIA® EWS-4

EMERGENCY WALL PAGING STATION



The EWS-4 is a wall-mounted networked paging station for use in Vocia systems. The EWS-4 features embedded DSP and on-board memory to support standard and advanced public address functionalities. The EWS-4 can store four user-configurable page codes. Additionally, all device-specific configuration information is stored locally, which means the EWS-4 does not rely on a centralized controller for processing and page routing. Thus, the processing, routing and storage functionality in a Vocia system is decentralized, which eliminates any centralized point of failure. As part of the Vocia system, the EWS-4 meets paging requirements for facilities of all sizes.

FEATURES

- Auxiliary port allows the use of an external 24V compliant power supply for main or redundant power
- Push-to-talk button with status indication
- Four user-configurable page codes
- Four software configurable emergency priority paging levels
- Supports up to 250 software-configurable paging priority levels
- Local digital signal processing, including gain, filters and compressor/limiter
- Local storage of configuration data
- Local storage of default and/or custom preambles
- Built-in store and forward functionality
- Backlit liquid crystal display (LCD) technology
- CobraNet® audio/control with dynamic use of available bundles, plus power over single Ethernet cable
- Optional PIN to restrict unauthorized use
- Auxiliary Port provides connection for power, line-level audio, and bi-directional RS232 for transmitting Vocia Text Protocol (VTP) commands
- High-quality, noise-cancelling handheld microphone
- Sturdy, surface-mounted component housing
- Rotary ID switches for unit identification
- EN 54-16 certified, CE marked, and RoHS compliant
- Covered by Biamp Systems' 5-year warranty

ARCHITECTS & ENGINEERS SPECIFICATION

The wall-mounted paging station shall be designed exclusively for use with Biamp® Vocia® systems. The wall-mounted paging station shall provide paging audio and control data via CobraNet,® and receive Power over Ethernet (PoE), utilizing a single (CAT5) network cable to a rear panel RJ-45 connector. Four buttons shall be provided on the front panel for assigning page codes with preambles. Multiple wall-mounted paging stations may be connected to a Vocia system by means of Ethernet switches. Four software configurable emergency priority paging levels shall be available. The wall station shall include override, store and forward, and lock-out capabilities. Each wall-mounted paging station shall provide local digital audio signal processing, local storage of configuration data, and standard and uploaded preambles in .WAV format. Wall-mounted paging stations shall possess a backlit LCD screen, PIN code accessibility, and a high-quality, noise-cancelling handheld microphone. The wall-mounted paging station is EN 54-16 certified, CE marked and shall be compliant with the RoHS directive. Warranty shall be five years. The wall-mounted paging station shall be a Vocia EWS-4.

VOCIA EWS-4 SPECIFICATIONS

Network Connection:	RJ-45 with shielded Ethernet (CAT5, CAT5e, CAT6 or CAT7)	Power:	
Frequency Response (100Hz - 20kHz):	+0, -1dB	PoE:	802.3af Class 2
THD+N (100Hz - 8kHz):	<0.05%	Aux:	24V DC 6W
Effective Input Headroom:	30dB	Overall Dimensions (excl. microphone):	
System Headroom:	18dB	Height:	5.3 inches (135 mm)
Gain:	Adjustable in 1dB steps over a 30dB range	Width:	11.9 inches (302 mm)
Maximum Input:	125dB SPL	Depth:	1.9 inches (48 mm)
Mic Type:	Noise cancelling dynamic microphone with dual transducer (monitored)	Weight:	2.6 lbs (1.2 kg)
Mic Pattern:	Cardioid	Mic Cord Length (extended):	4 ft. (1219 mm)
Mic Frequency Response:	100Hz-10kHz	Environment:	
Auxiliary Port:		Ambient Operating Temperature Range:	23-104° F (-5 - 40° C)
PTT:	Switch contact between pin and ground	Humidity:	0 - 95% non-condensing
12V DC Out:	50mA	Altitude:	0-10,000 Feet (0-3000 Meters) MSL
RS-232:	57600 kbps	Sample Rate:	48kHz
Balanced Line In:	-10dB Nominal	A/D Converters:	24-bit
Input Impedance:	3kΩ	Compliance:	
			EN 54-16 certified
			CE marked (Europe)
			UL and C-UL listed (USA and Canada)
			RCM (Australia)
			EAC (Eurasian Custom Union)
			RINA (Italy)
			RoHS Directive (Europe)
			EN 60849, AS 60849 verified

VOCIA EWS-4 WALL-MOUNTING BRACKETS

